

ITEMS	BATTERY NOX - 15"	BATTERY BOX - 18"	BATTERY BOX - 24"
MODEL NUMBER	STB-15I-OW	STB-18I-OW	STB-24I-OW
DIMENSIONS	24.5" (H) X 28.4" (D) X 15" (W)	24.5" (H) X 28.4" (D) X 18" (W)	24.5" (H) X 28.4" (D) X 24" (W)
BODY THICKNESS	3 MM OR 11 GAUGE	3 MM OR 11 GAUGE	3 MM OR 11 GAUGE
DOOR THICKNESS	11 GAUGE	11 GAUGE	11 GAUGE
CAPACITY	UP TO 350 LBS	UP TO 350 LBS	UP TO 350 LBS
WEIGHT	38 LBS	40 LBS	51 LBS
WIDTH	15"	18"	24"
FEATURES	T-LOCK WITH NYLON ROLLER	T-LOCK WITH NYLON ROLLER	DEPTH WITHOUT STEPS IS 19"
	HEAVY 8-GA ALUMINUM FOR YEARS OF PROTECTION	HEAVY 8-GA ALUMINUM FOR YEARS OF PROTECTION	HEAVY 8-GA ALUMINUM FOR YEARS OF PROTECTION
	OPEN WIDE ALUMINUM STEP BOX DESIGN	OPEN WIDE ALUMINUM STEP BOX DESIGN	OPEN WIDE ALUMINUM STEP BOX DESIGN
	BOX BODY AND LID 3.2 MM 5052 ALUMINUM SMOOTH PLATE	BOX BODY AND LID 3.2 MM 5052 ALUMINUM SMOOTH PLATE	BOX BODY AND LID 3.2 MM 5052 ALUMINUM SMOOTH PLATE
	STEPS MADE OF 2MM PUNCHED PLATE	STEPS MADE OF 2MM PUNCHED PLATE	STEPS MADE OF 2MM PUNCHED PLATE
	2 REINFORCED CORNERS AT BACK	2 REINFORCED CORNERS AT BACK	2 REINFORCED CORNERS AT BACK
	1 GAS STRUT TO HOLD LID OPEN	1 GAS STRUT TO HOLD LID OPEN	1 GAS STRUT TO HOLD LID OPEN
	SOLID WELDED SEAMS KEEP CARGO CLEAN AND DRY	SOLID WELDED SEAMS KEEP CARGO CLEAN AND DRY	SOLID WELDED SEAMS KEEP CARGO CLEAN AND DRY
	STEPS MADE OF PUNCHED PLATE AND AN OPEN WIDE DESIGN	STEPS MADE OF PUNCHED PLATE AND AN OPEN WIDE DESIGN	STEPS MADE OF PUNCHED PLATE AND AN OPEN WIDE DESIGN
	SUBBER SEAL FOR WEATHER RESISTANCE	SUBBER SEAL FOR WEATHER RESISTANCE	SUBBER SEAL FOR WEATHER RESISTANCE
	STEPS COME SEPARTELY TO AVOID DAMAGE DURING TRANSIT. THEY NEED TO BE BOLTED ON. ALL ACCESSORIES ARE INCLUDED WITH THE BOX	STEPS COME SEPARTELY TO AVOID DAMAGE DURING TRANSIT. THEY NEED TO BE BOLTED ON. ALL ACCESSORIES ARE INCLUDED WITH THE BOX	STEPS COME SEPARTELY TO AVOID DAMAGE DURING TRANSIT. THEY NEED TO BE BOLTED ON. ALL ACCESSORIES ARE INCLUDED WITH THE BOX
	ALL BOXES NEED TO BE INSTALLED WITH APPORPRIATE BRACKETS	ALL BOXES NEED TO BE INSTALLED WITH APPORPRIATE BRACKETS	ALL BOXES NEED TO BE INSTALLED WITH APPORPRIATE BRACKETS
	BOLTING THE BOXES TO THE FRAME WILL VOID THE WARRANTY	BOLTING THE BOXES TO THE FRAME WILL VOID THE WARRANTY	BOLTING THE BOXES TO THE FRAME WILL VOID THE WARRANTY
			